

Operating Instructions DRUMCLIP DC23C ORANGE

In combination with two Signode Tennax T2220 (19x0.89mm) straps.

DRUMCLIP DC23C ORANGE is an innovative tool that makes it **safer** and **easier** to secure ISO drums to a pallet, without the use of additional pallets or other equipment. This solution is EUMOS 40509 Transport Safe certified. This combination is useful for pallet stabilisation of 200 litre ISO Open Head drums on pallets.

Important information

- Check the Drumclip before use. A damaged Drumclip may not be used again.
- Check the production date on the upperside of the Drumclip. The Drumclip must not be used for longer than 2 years after the production date.
- The Drumclip can be cleaned with water and soap.
- If the Drumclip has been in contact with chemicals, it may no longer be used.
- Drumclips must be kept in dry, moderately heated conditions and protected from sunlight and mechanical damage.
- The Drumclip may not be dried or stored near fire or in places with elevated temperatures.

Step 1

Place four plastic drums on a wooden pallet.

Step 2

Place two Drumclips opposite each other between two drums with the wide side facing outwards. Use two Signode Tenax T2220 straps. One strap is stretched horizontally at the centre of the drums. The other strap is stretched vertically over the two Drumclips and under the pallet. Both straps are tensioned with a force of 2500 N. Now the pallet is safely certified according to EUMOS 40509 Transport Safe. The above step should be performed for each pallet with drums.

